

Manufacturers can offer more specific information, so go through the anchor section of this Buyer's Guide and get in touch with them directly. The anchors chosen for the tables are the most widely used but by no means comprise a complete list. Other anchors to consider include: The Max, Hans C-Anchor, the Tallon, Fluke, and Delta, to name just a few. New anchors are being developed all the time.

Anchor Weight Guide

BOAT SIZE		ANCHOR WEIGHT				
Length(ft)	Weight(lbs)	Bruce(lbs)	Danforth*(lbs)	Fortress(lbs)	Plow(lbs)	Yachtsman(lbs)
20-25	2,500	4.4	8-S, 5-H**	4	10	15
26-30	5,000	11	13-S, 12-H	7	15	25
31-35	10,000	11/16.5	22-S, 12-H	7/10	20	35-40
36-40	15,000	16.5	22-S, 20-H	10	25	50
41-45	20,000	22	40-S, 20-H	15	35	65
46-50	30,000	22/44	65-S, 35-H	21	45	75
51-60	50,000	44	85-S, 60-H	32	60	100

Anchor Rode Guide

BOAT SIZE		ANCHOR RODE		
Length (ft)	Weight (lbs)	Chain (dia.-inch)	Nylon (dia.-inch)	Length (ft)
20-25	2,500	3/16	7/16	90
26-30	5,000	1/4	7/16	135
31-35	10,000	5/16	1/2	190
36-40	15,000	3/8	9/16	225
41-45	20,000	7/16	5/8	240
46-50	30,000	1/2	11/16	315
51-60	50,000	9/16	3/4	360

*Danforth is a registered trademark. Similar-style anchors may differ significantly in performance. **S indicates standard anchor; B indicates high-tensile anchor

This article was found in the *SAIL 1997 Sailboat Buyers Guide*. Their Web Address is:
<http://www.sailbuyersguide.com/>

[Return to Boating Education Page](#)

[Return to Maritime History Main Page](#)